



floorwood designer timber flooring

+61 414974199  
info@floorwood.com.au  
www.floorwood.com.au

June, 2016

## VERSAILLES IN FRENCH OAK

Floorwood French Oak Versailles Panels are constructed by the traditional method of tongue & groove connecting all the beveled pieces to form the panel. They are held in place by a C-clip method on the reverse side of the frame. So no dowel pegs are required.



### Specifications:

- Specie: **Oak** (*Quercus robur*) origin-Northern France, Southern Germany
- All our timbers are European species labeled FSC or PEFC or from a sustainable source.
- Type: Solid, Commercial & Residential Use. Tongue and groove connected sections and sides.
- Size: 866mm x 866mm x 18mm
- Bevelled sections and sides.
- Shuttle blocks: Optional decorative border pieces with a tongue on both sides
- Grade - ABC
- Brinell hardness of oak - 5.5mm - 8mm wear layer 3.4-4.1 Janka scale: 1360 medium hardness
- Installation - Direct Stick Methods.
- Unfinished/raw/uncoated - Factory pre-finished available through custom order. Oil: Various manufacturers. Lacquered finishes can be requested.
- Warranty - Residential 25 year limited warranty on structural integrity of product. Commercial 7 year limited warranty on structural integrity of product.
- VOC Emission Rate - 0.05mg/m<sup>2</sup>/hr •Complies with Specification C1.10a Fire Hazard Properties: CRF. 4.5 or Greater SDR % - minute <750



Optional Shuttle Blocks Borders

Proprietary C clip Retention System



